

Wire Wheel Cleaner

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.
Issue date: 6/3/2022 Revision date: 6/3/2022 Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : Wire Wheel Cleaner
Product code : Part # C80

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Tire and Wheel Cleaner (All types but Aerosol)

1.3. Supplier

Manufacturer

Superior Products
6962 Highway 111
S. Roxana, IL 62087 - US
T 800 424-9300, Contact Phone: 618 254-7400 - F 618 254-7421
sds@superiorproducts.com

1.4. Emergency telephone number

Emergency number : 1-800-424-9300

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Flam. Liq. 4	Combustible liquid
Met. Corr. 1	May be corrosive to metals
Acute Tox. 2 (Oral)	Fatal if swallowed
Acute Tox. 3 (Inhalation:vapour)	Toxic if inhaled
Skin Corr. 1	Causes severe skin burns and eye damage
Eye Dam. 1	Causes serious eye damage
STOT RE 1	Causes damage to organs through prolonged or repeated exposure
HHNOC 1	Causes severe damage to the respiratory tract

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Danger

Hazard statements (GHS US) :

Combustible liquid
May be corrosive to metals
Fatal if swallowed
Causes severe skin burns and eye damage
Toxic if inhaled
Causes damage to organs through prolonged or repeated exposure
Causes severe damage to the respiratory tract

Precautionary statements (GHS US) :

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Keep only in original container.

Wire Wheel Cleaner

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Do not breathe dust/fume/gas/mist/vapors/spray.
Wash hands, forearms and face thoroughly after handling.
Do not eat, drink or smoke when using this product.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection.
If swallowed: Immediately call a poison center or doctor.
Rinse mouth.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
Wash contaminated clothing before reuse.
If inhaled: Remove person to fresh air and keep comfortable for breathing.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Immediately call a poison center or doctor.
Absorb spillage to prevent material-damage.
Store in a well-ventilated place. Keep cool.
Store locked up.
Store in corrosive resistant container with a resistant inner liner.
Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

Other hazards which do not result in classification : Use of alcoholic beverages enhances the harmful effect.

2.4. Unknown acute toxicity (GHS US)

5% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (vapors))

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%
Hydrofluoric acid	CAS-No.: 7664-39-3	*
Phosphoric acid	CAS-No.: 7664-38-2	*
2-Butoxyethanol	CAS-No.: 111-76-2	*
Poly(oxy-1,2-ethanediyl), .alpha.-(nonylphenyl)-.omega.-hydroxy-	CAS-No.: 9016-45-9	*

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : If inhaled: Remove person to fresh air and keep comfortable for breathing. Immediately call a poison center or doctor/physician. Give oxygen or artificial respiration if necessary.

First-aid measures after skin contact : If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Immediately call a POISON CENTER or doctor.

First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor/physician.

First-aid measures after ingestion : IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Rinse mouth. Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person.

Wire Wheel Cleaner

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation	: Toxic if inhaled. Causes burns to the respiratory system.
Symptoms/effects after skin contact	: Causes severe skin burns. Symptoms may include redness, pain, blisters.
Symptoms/effects after eye contact	: Causes serious eye damage. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. May cause burns.
Symptoms/effects after ingestion	: Fatal if swallowed. May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.

4.3. Immediate medical attention and special treatment, if necessary

Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Dry chemical powder, alcohol-resistant foam, carbon dioxide (CO ₂). Water spray.
Unsuitable extinguishing media	: Do not use water jet.

5.2. Specific hazards arising from the chemical

Fire hazard	: Combustible liquid. Products of combustion may include, and are not limited to: oxides of carbon.
-------------	---

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Move containers away from the fire area if this can be done without risk. Cool closed containers exposed to fire with water spray.
Protection during firefighting	: Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Use special care to avoid static electric charges. Eliminate ignition sources.
------------------	---

6.1.1. For non-emergency personnel

Emergency procedures	: Do not touch or walk on the spilled product.
----------------------	--

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

For containment	: Remove all sources of ignition. Stop leak if safe to do so. Absorb and/or contain spill with inert material (sand, vermiculite or other appropriate material), then place in suitable container. Do not flush into surface water or sewer system. Wear recommended personal protective equipment.
Methods for cleaning up	: Sweep or shovel spills into appropriate container for disposal. Provide ventilation. Absorb spillage to prevent material-damage.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection".

Wire Wheel Cleaner

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed	: May be corrosive to metals.
Precautions for safe handling	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not get in eyes, on skin, or on clothing. Do not breathe dust, fume, gas, mist, spray, vapors. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke. Use only outdoors or in a well-ventilated area. Use only non-sparking tools. Wear personal protective equipment.
Hygiene measures	: Take off immediately all contaminated clothing and wash it before reuse. Contaminated work clothing should not be allowed out of the workplace. Wash hands, forearms and face thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Keep out of the reach of children. Keep only in original container. Store tightly closed in a dry, cool and well-ventilated place. Keep cool. Store away from other materials. Protect from moisture. Store locked up. Store in corrosive resistant container with a resistant inner liner.
Incompatible materials	: Refer to Section 10 on Incompatible Materials.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Wire Wheel Cleaner	
No additional information available	
Hydrofluoric acid (7664-39-3)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA [ppm]	0.5 ppm
ACGIH OEL Ceiling [ppm]	2 ppm
ACGIH chemical category	Skin - potential significant contribution to overall exposure by the cutaneous route
USA - ACGIH - Biological Exposure Indices	
BEI (BLV)	3 mg/g Kreatinin Parameter: Fluoride - Medium: urine - Sampling time: prior to shift (background, nonspecific) 10 mg/g Kreatinin Parameter: Fluoride - Medium: urine - Sampling time: end of shift (background, nonspecific)
USA - OSHA - Occupational Exposure Limits	
OSHA PEL (TWA) [2]	3 ppm
Phosphoric acid (7664-38-2)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	1 mg/m ³
ACGIH OEL STEL	3 mg/m ³

Wire Wheel Cleaner

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Phosphoric acid (7664-38-2)	
USA - OSHA - Occupational Exposure Limits	
OSHA PEL (TWA) [1]	1 mg/m ³
Poly(oxy-1,2-ethanediyl), .alpha.-(nonylphenyl)-.omega.-hydroxy- (9016-45-9)	
No additional information available	
2-Butoxyethanol (111-76-2)	
USA - ACGIH - Occupational Exposure Limits	
Local name	2-Butoxyethanol (EGBE)
ACGIH OEL TWA [ppm]	20 ppm
Remark (ACGIH)	TLV® Basis: Eye & URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI
ACGIH chemical category	Confirmed Animal Carcinogen with Unknown Relevance to Humans
Regulatory reference	ACGIH 2020
USA - ACGIH - Biological Exposure Indices	
BEI (BLV)	200 mg/g Kreatinin Parameter: Butoxyacetic acid with hydrolysis - Medium: urine - Sampling time: end of shift
USA - OSHA - Occupational Exposure Limits	
Local name	2-Butoxyethanol
OSHA PEL (TWA) [1]	240 mg/m ³
OSHA PEL (TWA) [2]	50 ppm
Limit value category (OSHA)	prevent or reduce skin absorption
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

8.2. Appropriate engineering controls

Appropriate engineering controls	: Ensure good ventilation of the work station. Provide readily accessible eye wash stations and safety showers.
Environmental exposure controls	: Avoid release to the environment.

Wire Wheel Cleaner

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Wear suitable gloves resistant to chemical penetration

Eye protection:

Wear eye/face protection

Skin and body protection:

Wear suitable protective clothing. Long sleeved protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Other information:

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Tan liquid
Color	: Tan
Odor	: Acidic
Odor threshold	: No data available
pH	: 2
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Combustible liquid
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Solubility	: Water: completely soluble
Partition coefficient n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use. May be corrosive to metals.

Wire Wheel Cleaner

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

10.2. Chemical stability

Stable under normal conditions. May form flammable/explosive vapor-air mixture.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Moisture. Heat. Incompatible materials. Sources of ignition.

10.5. Incompatible materials

Acids. Bases. Oxidizing agent. Metals.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon. May release flammable gases.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Fatal if swallowed.
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Toxic if inhaled.

Wire Wheel Cleaner	
ATE US (oral)	38.148 mg/kg body weight
ATE US (vapors)	5.851 mg/l/4h
Unknown acute toxicity (GHS US)	5% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (vapors))
Hydrofluoric acid (7664-39-3)	
LC50 inhalation rat	0.79 mg/l (Exposure time: 1 h)
Phosphoric acid (7664-38-2)	
LD50 oral rat	1530 mg/kg
LD50 dermal rabbit	2740 mg/kg
Poly(oxy-1,2-ethanediyl), .alpha.-(nonylphenyl)-.omega.-hydroxy- (9016-45-9)	
LD50 oral rat	2590 mg/kg
LD50 dermal rabbit	1780 µl/kg
2-Butoxyethanol (111-76-2)	
LD50 oral rat	470 mg/kg
LC50 inhalation rat	486 ppm/4h

Skin corrosion/irritation : Causes severe skin burns.
pH: 2
Serious eye damage/irritation : Causes serious eye damage.
pH: 2
Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

Wire Wheel Cleaner

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

2-Butoxyethanol (111-76-2)	
IARC group	3 - Not classifiable
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
2-Butoxyethanol (111-76-2)	
STOT-single exposure	May cause drowsiness or dizziness. May cause respiratory irritation.
STOT-repeated exposure	: Causes damage to organs through prolonged or repeated exposure.
Hydrofluoric acid (7664-39-3)	
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available
Symptoms/effects after inhalation	: Toxic if inhaled. Causes burns to the respiratory system.
Symptoms/effects after skin contact	: Causes severe skin burns. Symptoms may include redness, pain, blisters.
Symptoms/effects after eye contact	: Causes serious eye damage. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. May cause burns.
Symptoms/effects after ingestion	: Fatal if swallowed. May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Other information	: Likely routes of exposure: ingestion, inhalation, skin and eye.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.

Wire Wheel Cleaner

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Hydrofluoric acid (7664-39-3)	
LC50 - Fish [1]	51 mg/l Test organisms (species): other:summary of findings in various species
EC50 - Crustacea [1]	270 mg/l (Exposure time: 48 h - Species: Daphnia species)
LC50 - Fish [2]	165 mg/l Test organisms (species): other:summary of findings in various species
NOEC (chronic)	14.1 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	4 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '21 d'

Phosphoric acid (7664-38-2)	
LC50 - Fish [1]	75.1 mg/l
EC50 - Crustacea [1]	> 100 mg/l Test organisms (species): Daphnia magna

2-Butoxyethanol (111-76-2)	
LC50 - Fish [1]	1490 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
EC50 - Crustacea [1]	> 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 - Fish [2]	2950 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus)

12.2. Persistence and degradability

Wire Wheel Cleaner	
Persistence and degradability	Not established.

12.3. Bioaccumulative potential

Wire Wheel Cleaner	
Bioaccumulative potential	Not established.

Hydrofluoric acid (7664-39-3)	
BCF - Fish [1]	(no bioaccumulation)
Partition coefficient n-octanol/water	-1.4

2-Butoxyethanol (111-76-2)	
Partition coefficient n-octanol/water	0.81 (at 25 °C)

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other information : No other effects known.

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations : Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation. Empty containers may contain residues which are hazardous.

Additional information : Handle empty containers with care because residual vapors are flammable.

Ecology - waste materials : Hazardous waste due to toxicity.

Wire Wheel Cleaner

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

SECTION 14: Transport information

In accordance with DOT

14.1. UN number

DOT NA No : UN2922

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Corrosive liquids, toxic, n.o.s. (HYDROGEN FLUORIDE, 2-BUTOXYETHANOL)

14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT) : 8 (6.1)

Hazard labels (DOT) : 8, 6.1



14.4. Packing group

Packing group (DOT) : II

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

Special transport precautions : Do not handle until all safety precautions have been read and understood.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

15.2. International regulations

No additional information available

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16: Other information

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Wire Wheel Cleaner

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Issue date : 06/03/2022
Revision date : 06/03/2022
Other information : None.
Prepared by : Nexreg Compliance Inc.
www.Nexreg.com



Full text of H-phrases	
Acute Tox. 2 (Oral)	Acute toxicity (oral) Category 2
Acute Tox. 3 (Inhalation:vapour)	Acute toxicity (inhalation:vapor) Category 3
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Flam. Liq. 4	Flammable liquids Category 4
HHNOC 1	Health hazard not otherwise classified, category 1
Met. Corr. 1	Corrosive to metals Category 1
Skin Corr. 1	Skin corrosion/irritation Category 1
STOT RE 1	Specific target organ toxicity (repeated exposure) Category 1

Safety Data Sheet (SDS), USA

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.