



Ceramic 5000 Paint Coating Kit

Safety Data Sheet
Revision Date: 6/8/2021

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : A50 - Ceramic 5000 Paint
Product code Coating Kit : 32401

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Surface Coating

1.3. Supplier

Superior Products
6962 Highway 111
S. Roxana, IL, 62087
US
T 800 424-9300, Contact Phone: 618 254-7400 - F 618 254-7421
sds@superiorproducts.com

1.4. Emergency telephone number

Emergency Phones: Chemtrec 1-800-424-9300

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

Hazard Classification:

Physical Hazards

Flammable liquids

Category 3

Health Hazards :

not applicable

OSHA Specified Hazards:

not applicable

Warning label items including precautionary statement:

Pictogram:



Ceramic 5000 Paint Coating Kit

Safety Data Sheet
Revision Date: 6/8/2021



Signal words: DANGER!

HAZARD STATEMENT(S): H226: flammable liquid and vapor.

Precautionary statement:

Prevention:

P210: Keep away from heat/sparks/open flames/hot surfaces.
No Smoking.
P233: Keep container tightly closed.
P240: Ground/bond container and receiving equipment.
P241: Use explosion-proof electrical /ventilating/ lighting/
Equipment.
P242: Use only non-sparking tools.
P243: Take precautionary measures against static discharge.
P280: Wear protective gloves/protective clothing/eye
Protection/ face protection.

Response:

P303+P361+P353: If on skin (or hair): Remove/take off
Immediately all contaminated clothing. Rinse skin with
water/ shower.
P370+P378: In case of fire; Use water spray, carbon dioxide,
Dry chemical or alcohol foam for extinction.

P310: Immediately call a Poison Center or doctor/physician.

Storage:

P403:+P235: Store in a well- ventilated place. Keep container
tightly closed. Keep Cool.

Disposal:

P501: Dispose of content/container to an appropriate
Treatment and disposal facility in accordance with applicable
Laws regulations and product characteristic at time of
disposal.



Ceramic 5000 Paint Coating Kit

Safety Data Sheet
Revision Date: 6/8/2021

Hazard(s) not otherwise Potential peroxide former.
Classified (HNOC): None as defined under 29 CFR 1900.1200.

SECTION 3: Composition/Information on ingredients

Substances/ Mixtures

General information:

| Chemical name | Concentration | Additional identification |
|---|---------------|---------------------------|
| Proprietary Resin | N/A | N/A |
| Ethyl 3-ethoxypropionate | 90% | Cas-No: 763-69-9 |
| Butylated hydroxytoluene | <0.1% | Cas-No: 128-37-0 |
| Acetic Acid, C9-11 branched Alkyl ester | 1-5% | Cas-No: 108419-34-7 |

*All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume. This substance has workplace exposure limit(s).

SECTION 4: First-aid measures

4.1. Description of first aid measures

| | |
|---------------------------------------|---|
| First-aid measures after inhalation | : If inhaled: Move to fresh air. Treat symptomatically. Get medical attention if symptoms persist. |
| First-aid measures after skin contact | : If on skin (or hair): Wash with soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing before reuse. Destroy or thoroughly clean contaminated shoes |
| First-aid measures after eye contact | : IF IN EYES: Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention. |
| First-aid measures after ingestion | : IF SWALLOWED: Seek medical advice. |

4.2. Most important symptoms and effects (acute and delayed)

No known chronic or acute health risks. :
Indication of any immediate medical attention and special treatment needed.
Hazards: None known.
Treatment: Treat symptomatically.



Ceramic 5000 Paint Coating Kit

Safety Data Sheet
Revision Date: 6/8/2021

SECTION 5: Fire-fighting measures

| | |
|--|--|
| General fire hazards: | Flammable liquid and vapor. USE WATER WITH CAUTION. Material will float and may ignite on surface of water. Use water spray to keep fire-exposed containers cool. |
| Extinguishing media Suitable extinguishing media: | Water spray. Dry chemical. Carbon Dioxide, Foam. |
| Unsuitable extinguishing Media: | None known. |
| Special hazards arising from the substance or mixture: | Vapors may cause a flash fire or ignite explosively. Vapors may travel considerable distance to a source of ignition and flash back. Prevent buildup of vapors or gases to explosive concentrations. |
| Advice for firefighters Special fire-fighting procedures: | Water may be ineffective in fighting the fire. Use water spray to keep fire exposed containers cool. |
| Special protective Equipment for fire-fighters: | Self-contained breathing apparatus and full protective clothing must be worn in case of fire. |

SECTION 6: Accidental release measures

| | |
|---|---|
| Personal precautions, Protective equipment and emergency procedures: | Wear appropriate personal protective equipment. |
| Environmental precautions: | Avoid release to environment. |
| Methods and material for Containment and cleaning up: | Eliminate the sources of ignition. Absorb spills with vermiculite or other inert material, then place in a container for chemical waste. Larger spills use water spray to disperse vapors and dilute spill to a non-flammable mixture. Prevent any runoff from entering any drains, sewers or streams. Dike for later disposal. |
| Notification Procedures: | In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations. |

SECTION 7: Handling and storage

7.1. Precautions for safe handling

| | |
|---------------------------------------|--|
| Precautions for safe handling: | Avoid breathing mist or vapors. Avoid contact with eyes And prolonged or repeated contact with skin. Use only with adequate ventilation. Wash hands thoroughly after handling. |
|---------------------------------------|--|



Ceramic 5000 Paint Coating Kit

Safety Data Sheet
Revision Date: 6/8/2021

Conditions for safe storage, including any incompatibilities:

Keep container tightly closed and in well-ventilated place.

Specific end use(s):

Vehicle Surface Coating

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

County specific exposure limits have not been established or are not applicable unless listed below.

| Chemical name: | Type: | Exposure limit values: | Source: |
|--------------------------|-------------------|---------------------------------------|---|
| Ethyl 3-ethoxypropionate | TWA | 50 ppm occupational exposure limit | Eastman Chemical Company |
| | (12 2000) STEL | 100 ppm | Eastman Chemical Company Occupational exposure limit (12 20000) |

Exposure controls

Good general ventilation should be used.

Controls: If applicable use local exhaust ventilation or other engineering to maintain airborne levels below recommended

Appropriate engineering

exposure limits. controls

Individual protection measures, such as personal protective equipment

General information: This is a solvent based product, safety glasses and chemical resistant gloves should be worn while using this product.

Respiratory protection: If engineering controls do not maintain airborne concentrations below recommended exposure limits or to an acceptable level in countries where exposure limits have not been established an approved respirator must be worn.

SECTION 9: Physical and chemical properties

The physical and chemical properties are provide for safety, health and environmental considerations only and may not fully represent the product specification. For more information contact the supplier.

| | | |
|-------------------------------|------------------------------|---------------|
| Appearance | liquid | |
| Oder: | ESTER | |
| Order threshold: | 0.02PPM | |
| Ph: | no data | |
| Melting point/freezing point: | no data | boiling point |
| | 85 degrees Celsius | |
| Flash point: | 59° C (Setaflash Closed Cup) | |
| Evaporation rate: | no data | |
| Flammability: | Flammable | |
| Upper flammability: | no data | |
| Lower flammability | no data | |
| Vapor pressure: | no data | |
| Vapor density: air=1 | 5.0 | |



Ceramic 5000 Paint Coating Kit

Safety Data Sheet
Revision Date: 6/8/2021

| | |
|--|-------------------------------|
| Density: | 870 kg/m ³ |
| Solubility(ies): | water-no, others -no |
| Partition coefficient: n-octanol/water | no data |
| Auto-ignition: | 377° C (ASTM E659) |
| Decomposition temperature: | Thermal stability not tested. |
| Viscosity: | 0.8 mPa.s@20°C |
| Specific Gravity: | 0.87 |

SECTION 10: Stability and reactivity

10.1. Reactivity

None known

10.2. Chemical stability

Stable

10.3. Possibility of hazardous reactions

Forms peroxides of unknown stability.

10.4. Conditions to avoid

Heat, sparks, flames.

10.5. Incompatible materials

Oxidizing material can cause a reaction.

10.6. Hazardous decomposition products

Carbon Dioxide and Carbon Monoxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

| | |
|----------------------|---|
| Inhalation: | None known |
| Ingestion: | none known |
| Skin contact: | prolonged or repeated skin contact may cause drying, cracking or irritation |
| Eye contact: | none known |

Information on toxicological effects

Acute Toxicity

| | |
|---|---|
| Oral product: | No Data available |
| Dermal product: | dermal LD-50:Rabbit, Male: > 4080 mg/kg |
| Inhalation product: | No Data Available. |
| Skin corrosion/irritation product: | No data available. |
| Serious eye damage/eye irritation product: | No data |
| Respiratory or skin sensitization product: | No data |

Mutagenicity

In vitro: n/a



Ceramic 5000 Paint Coating Kit

Safety Data Sheet
Revision Date: 6/8/2021

In vivo: n/a
Carcinogenicity product: n/a
Specified substance: n/a
Reproductive toxicity product: n/a
Specified substance n/a
Specific target organ toxicity-single exposure: n/a
Specified substance: n/a
Specific target organ toxicity-repeated exposure: n/a
Specified substance: n/a
Aspiration hazards product: n/a
Specified substance: n/a
Other adverse effects: n/a

SECTION 12: Ecological information

All work practices must be aimed at eliminating environmental contamination.
Effects of material on plants and animals:
This product may be harmful or fatal to plants and animal life if released into the environment.
Effect of material on aquatic life:
The most sensitive known aquatic group to any component of this product is:
Fish: LC-50 (golden orfe, 48 h):265-360 mg/l
Keep out of sewers and natural water supplies.
This material is a mobile liquid.
Degradability: 76% (20 days, ready biodegradability: closed bottle test.) Readily biodegradable
This product does not accumulate or bio magnify in the environment.

SECTION 13: Disposal considerations

13.1. Disposal methods

All disposals must be in accordance with all federal, state, provincial, and local regulations. If in doubt, contact proper agencies. EPA characteristic: D001

SECTION 14: Transport information

DOT : Shipping Description, UN1866, Resin Solution, 3, III
IMGD: International Maritime Dangerous Goods Code
Shipping Description, UN1866, Resin Solution, 3,III
IATA: Shipping Description, UN1866, Resin Solution, 3, III



Ceramic 5000 Paint Coating Kit

Safety Data Sheet
Revision Date: 6/8/2021

SECTION 15: Regulatory information

Safety, health and environmental regulation/legislation specific for the substance or mixture:

This product has been classified in accordance with hazard criteria of the controlled products regulations and the MSDS contains all the information required by the controlled products regulations.

WHMIS (Canada) Status: Controlled

WHMIS (Canada) Hazard Classification: B/3

SARA 311-312 Hazard Classification (S):

Immediate (acute) health hazard fire hazard

US EPCRA (SARA Title III) Section 313- Toxic chemical list

None

OSHA: hazardous

TSCA (US toxic Substance control act): This product is listed on the TSCA inventory. Any impurities present in this product are exempt from listing.

DSL (Canadian Domestic List) and CEPA (Canadian Environmental Protection Act): This product is listed on the DSL or otherwise complies with CEPA new substance notification requirements.

AICS/NICNAS (Australian Inventory of Chemical Substances and National Industrial Chemicals Notification and Assessment Scheme): This product is listed on AICS or otherwise complies with NICNAS.

MITI (Japanese Handbook of Existing and New Chemical Substances):

All components of this product are listed in the handbook or have been approved in japan by new substance notification.

ECL (KOREAN TOXIC Substances Control Act): All components of this product are listed on the Korean inventory or otherwise comply with the Korean Toxic Substances Control Act.

SECTION 16: Other information

HMS Hazard Ratings: Health-1 Flammability-3, Chemical Reactivity-0

Revision Information: Not Relevant.

Issue date: 04-08-15

Disclaimer: This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.