

SAFETY DATA SHEET

Issuing Date No data available

Revision Date 04-Jun-2015

Revision Number 3



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Name Muscle Magic

Other means of identification

UN-No. UN1760

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Degreaser - General Purpose - Non-Aerosol

Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier Name Superior Products Co

Supplier Address 6962 Highway 111
S. Roxana
L
62087
US

Supplier Phone Number Phone:618 254-7400
Fax:618 254-7421

Supplier Email sds@superiorproducts.com

Emergency telephone number

Company Emergency Phone Number 800 424-9300

2. HAZARDS IDENTIFICATION


Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200).

Skin corrosion/irritation	Category 1 Sub-category B
Serious eye damage/eye irritation	Category 1



GHS Label elements, including precautionary statements**Emergency Overview**

Signal word	Danger
Hazard Statements Causes severe skin burns and eye damage	
	
Appearance Purple	Physical state Liquid
Odor Mild chemical	

Precautionary Statements - Prevention

Do not breathe dust/fume/gas/mist/vapors/spray
Wash face, hands and any exposed skin thoroughly after handling
Wear protective gloves/protective clothing/eye protection/face protection

Precautionary Statements - Response

Immediately call a POISON CENTER or doctor/physician
Specific treatment (see supplemental first aid instructions on this label)

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
Immediately call a POISON CENTER or doctor/physician

Skin

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
Wash contaminated clothing before reuse

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
Immediately call a POISON CENTER or doctor/physician

Ingestion

IF SWALLOWED: Rinse mouth. DO NOT induce vomiting

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Unknown Toxicity

0% of the mixture consists of ingredient(s) of unknown toxicity

Other information

Harmful to aquatic life with long lasting effects

Interactions with Other Chemicals

Use of alcoholic beverages may enhance toxic effects.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%	Trade Secret
2-Butoxyethanol	111-76-2	1 - 5	*
Sodium hydroxide	1310-73-2	1 - 5	*
Quaternary ammonium compounds, coco alkylbis(hydroxyethyl)methyl, ethoxylated, chlorides	61791-10-4	1-5	*
Sodium metasilicate	6834-92-0	1 - 5	*
Tetrasodium EDTA	64-02-8	1 - 5	*

*The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

First aid measures**General Advice**

Immediate medical attention is required. Show this safety data sheet to the doctor in attendance.

Eye contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Seek immediate medical attention/advice.

Skin contact

Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Seek immediate medical attention/advice.

Inhalation

Remove to fresh air. If breathing is difficult, (trained personnel should) give oxygen. If not breathing, give artificial respiration. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation.

Ingestion

Do NOT induce vomiting. Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately.

Self-protection of the first aider Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation.

Most important symptoms and effects, both acute and delayed

Most Important Symptoms and Effects Burning sensation.

Indication of any immediate medical attention and special treatment needed

Notes to Physician

Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Do not give chemical antidotes. Asphyxia from glottal edema may occur. Marked decrease in blood pressure may occur with moist rales, frothy sputum, and high pulse pressure.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Dry chemical. Carbon dioxide (CO₂). Water spray.

Unsuitable extinguishing media

CAUTION: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

Some are oxidizers and may ignite combustibles (wood, paper, oil, clothing, etc.).

Uniform Fire Code

Corrosive: Other-Liquid

Hazardous Combustion Products

Carbon oxides.

Explosion Data

Sensitivity to Mechanical Impact No.

Sensitivity to Static Discharge No.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures**Personal precautions**

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Stop leak if you can do it without risk.

Other Information

DO NOT GET WATER INSIDE CONTAINERS.

Environmental precautions**Environmental precautions**

Prevent entry into waterways, sewers, basements or confined areas.

Methods and material for containment and cleaning up**Methods for containment**

Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers.

Methods for cleaning up

Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.



7. HANDLING AND STORAGE

Precautions for safe handling

Handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. In case of insufficient ventilation, wear suitable respiratory equipment. Use only with adequate ventilation and in closed systems. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse.

Conditions for safe storage, including any incompatibilities

Storage Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from moisture. Store locked up. Keep out of the reach of children. Store away from other materials.

Incompatible Products Acids. Bases. Oxidizing agent.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
2-Butoxyethanol 111-76-2	TWA: 20 ppm	TWA: 50 ppm TWA: 240 mg/m ³ (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m ³ (vacated) S*	IDLH: 700 ppm TWA: 5 ppm TWA: 24 mg/m ³
Sodium hydroxide 1310-73-2	Ceiling: 2 mg/m ³	TWA: 2 mg/m ³ (vacated) Ceiling: 2 mg/m ³	IDLH: 10 mg/m ³ Ceiling: 2 mg/m ³

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits Immediately Dangerous to Life or Health

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992) See section 15 for national exposure control parameters

Appropriate engineering controls

Engineering Measures Showers
Eyewash stations
Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection Face protection shield.

Skin and body protection Wear protective gloves and protective clothing. Long sleeved clothing. Chemical resistant apron. Impervious gloves.

Respiratory protection No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or

smoke when using this product. Take off contaminated clothing and wash before reuse. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. For environmental protection, remove and wash all contaminated protective equipment before re-use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Physical state Appearance Color	Liquid Purple No information available	Odor Odor Threshold	Mild chemical No information available
--	--	--------------------------------------	---

Property	Values	Remarks Method
pH	11	None known
Melting / freezing point	No data available	None known
Boiling point / boiling range	No data available	None known
Flash Point	No data available	None known
Evaporation Rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		
Upper flammability limit	No data available	
Lower flammability limit	No data available	
Vapor pressure	No data available	None known
Vapor density	No data available	None known
Specific Gravity	1.1	None known
Water Solubility	Completely soluble	None known
Solubility in other solvents	No data available	None known
Partition coefficient: n-octanol/water	No data available	None known
Autoignition temperature	No data available	None known
Decomposition temperature	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known
Explosive properties	No data available	
Oxidizing properties	No data available	

Other Information

Softening Point VOC Content (%) Particle Size Particle Size Distribution	No data available No data available No data available
---	---

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

Exposure to air or moisture over prolonged periods.

Incompatible materials

Acids. Bases. Oxidizing agent.

Hazardous Decomposition Products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation

Specific test data for the substance or mixture is not available. Corrosive by inhalation. (based on components). Inhalation of corrosive fumes/gases may cause coughing, choking, headache, dizziness, and weakness for several hours. Pulmonary edema may occur with tightness in the chest, shortness of breath, bluish skin, decreased blood pressure, and increased heart rate. Inhaled corrosive substances can lead to a toxic edema of the lungs. Pulmonary edema can be fatal. May cause irritation of respiratory tract.

Eye contact

Specific test data for the substance or mixture is not available. Causes burns. (based on components). Corrosive to the eyes and may cause severe damage including blindness. Causes serious eye damage. May cause irreversible damage to eyes.

Skin contact

Specific test data for the substance or mixture is not available. Corrosive. (based on components). Causes burns.

Ingestion

Specific test data for the substance or mixture is not available. Causes burns. (based on components). Ingestion causes burns of the upper digestive and respiratory tracts. May cause severe burning pain in the mouth and stomach with vomiting and diarrhea of dark blood. Blood pressure may decrease. Brownish or yellowish stains may be seen around the mouth. Swelling of the throat may cause shortness of breath and choking. May cause lung damage if swallowed. May be fatal if swallowed and enters airways. Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
2-Butoxyethanol 111-76-2	470 mg/kg (Rat)	220 mg/kg (Rabbit)	450 ppm (Rat) 4 h
Sodium hydroxide 1310-73-2	-	1350 mg/kg (Rabbit)	-
Sodium metasilicate 6834-92-0	600 mg/kg (Rat)	-	-

Information on toxicological effects

Symptoms Erythema (skin redness). Burning. May cause blindness. Coughing and/ or wheezing.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.

Mutagenic Effects No information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
2-Butoxyethanol 111-76-2	A3	Group 3		

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 3 - Not Classifiable as to Carcinogenicity in Humans

Reproductive toxicity No information available.

STOT - single exposure No information available.

STOT - repeated exposure No information available.

Chronic Toxicity Chronic exposure to corrosive fumes/gases may cause erosion of the teeth followed by jaw necrosis. Bronchial irritation with chronic cough and frequent attacks of pneumonia are common. Gastrointestinal disturbances may also be seen. May cause adverse effects on the bone marrow and blood-forming system. May cause adverse liver effects. Carcinogenic potential is unknown.

Target Organ Effects Respiratory system. Eyes. Skin. Gastrointestinal tract (GI). Blood. Central Nervous System (CNS). Hematopoietic system. Kidney. Liver. Systemic Toxicity.

Aspiration Hazard No information available.

Numerical measures of toxicity Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)

5,203.00 mg/kg

ATEmix (dermal)

17,616.00 mg/kg (ATE)

ATEmix (inhalation-dust/mist)

39.50 mg/l

ATEmix (inhalation-vapor)

289.00 ATEmix

12. ECOLOGICAL INFORMATION

Ecotoxicity

Harmful to aquatic life with long lasting effects.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
2-Butoxyethanol 111-76-2		96h LC50: = 1490 mg/L (Lepomis macrochirus) 96h LC50: = 2950 mg/L (Lepomis macrochirus)		48h EC50: > 1000 mg/L 24h EC50: 1698 - 1940 mg/L
Sodium hydroxide 1310-73-2		96h LC50: = 45.4 mg/L (Oncorhynchus mykiss)		
Sodium metasilicate 6834-92-0		96h LC50: = 210 mg/L (Brachydanio rerio)		96h EC50: = 216 mg/L
Tetrasodium EDTA 64-02-8	72h EC50: = 1.01 mg/L (Desmodesmus subspicatus)	96h LC50: = 41 mg/L (Lepomis macrochirus) 96h LC50: = 59.8 mg/L (Pimephales promelas)		24h EC50: = 610 mg/L

Persistence and Degradability

No information available.

Bioaccumulation

Chemical Name	Log Pow
2-Butoxyethanol 111-76-2	0.51

Other adverse effects

No information available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal methods	This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).
Contaminated Packaging	Dispose of contents/containers in accordance with local regulations.
US EPA Waste Number	D002

California Hazardous Waste Codes 561

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Sodium hydroxide 1310-73-2	Toxic Corrosive

14. TRANSPORT INFORMATION

DOT



UN-No.	UN1760
Proper Shipping Name	CORROSIVE LIQUIDS, N.O.S.
Hazard Class	8
Packing Group	I
Description	UN1760, CORROSIVE LIQUIDS, N.O.S. (SODIUM METASILICATE), 8, II
Emergency Response Guide Number	154

TDG

UN-No.	UN1760
Proper Shipping Name	CORROSIVE LIQUID, N.O.S.
Hazard Class	8
Packing Group	I
Description	UN1760, CORROSIVE LIQUID, N.O.S. (SODIUM METASILICATE), 8, II

MEX

UN-No.	UN1760
Proper Shipping Name	CORROSIVE LIQUID, N.O.S.
Hazard Class	8
Packing Group	I
Description	UN1760, CORROSIVE LIQUID, N.O.S. (SODIUM METASILICATE), 8, II

ICAO

UN-No.	UN1760
Proper Shipping Name	CORROSIVE LIQUID, N.O.S.
Hazard Class	8
Packing Group	I
Description	UN1760, CORROSIVE LIQUID, N.O.S. (SODIUM METASILICATE), 8, II

IATA

UN-No.	UN1760
Proper Shipping Name	CORROSIVE LIQUID, N.O.S.
Hazard Class	8
Packing Group	I
Description	UN1760, CORROSIVE LIQUID, N.O.S. (SODIUM METASILICATE), 8, II

IMDG/IMO

UN-No.	UN1760
Proper Shipping Name	CORROSIVE LIQUID, N.O.S.
Hazard Class	8
Packing Group	I
EmS-No.	F-A, S-B
Description	UN1760, CORROSIVE LIQUID, N.O.S. (SODIUM METASILICATE), 8, II

RID

UN-No.	UN1760
Proper Shipping Name	CORROSIVE LIQUID, N.O.S.
Hazard Class	8
Packing Group	I
Classification code	C9
Description	UN1760, CORROSIVE LIQUID, N.O.S. (SODIUM METASILICATE), 8, II

ADR

UN-No.	UN1760
Proper Shipping Name	CORROSIVE LIQUID, N.O.S.
Hazard Class	8
Packing Group	I
Classification code	C9
Tunnel restriction code	(E)
Description	UN1760, CORROSIVE LIQUID, N.O.S. (SODIUM METASILICATE), 8, II

ADN

UN-No.	UN1760
Proper Shipping Name	CORROSIVE LIQUID, N.O.S.
Hazard Class	8
Packing Group	I
Classification code	C9
Special Provisions	274
Description	UN1760, CORROSIVE LIQUID, N.O.S. (SODIUM METASILICATE), 8, II
Hazard Labels	8
Limited Quantity	1L

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL	All components are listed either on the DSL or NDSL.
IECSC	-

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
 DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
2-Butoxyethanol - 111-76-2	111-76-2	1 - 5	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	(Ye)
Chronic Health Hazard	(N)
Fire Hazard	Nb
Sudden release of pressure hazard	Nb
Reactive Hazard	Nb

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Sodium hydroxide 1310-73-2	1000lb			X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Sodium hydroxide 1310-73-2	1000lb		RQ 1000 lb final RQ RQ 454 kg final RQ

US State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals.



U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
2-Butoxyethanol 111-76-2	X	X	X	X	X
Sodium hydroxide 1310-73-2	X	X	X	X	

International Regulations**Mexico****National occupational exposure limits**

Component	Carcinogen Status	Exposure Limits
2-Butoxyethanol 111-76-2 (1 - 5)		Mexico: TWA 26 ppm Mexico: TWA 120 mg/m ³ Mexico: STEL 75 ppm Mexico: STEL 360 mg/m ³
Sodium hydroxide 1310-73-2 (1 - 5)		Mexico: Ceiling 2 mg/m ³

Mexico - Occupational Exposure Limits - Carcinogens

Canada**WHMIS Hazard Class**

Not determined

16. OTHER INFORMATION

NFPA	Health Hazards 3	Flammability 1	Instability 0	Physical and Chemical Hazards -
HMIS	Health Hazards 3	Flammability 1	Physical Hazard 0	Personal Protection X

Prepared By

Product Stewardship
23 British American Blvd.
Latham, NY 12110
1-800-572-6501

Revision Date

04-Jun-2015

Revision Note

No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet